



SAFETYDATASHEET

Lithium Manganese Button Cell CR2025

Product Name: PK 3V 150mAh

Effective Date: 2021–08–18

Compiler: Zhoujuefer

Checker: Liu Lindiu

Approver: Thangxinogin

Shanghai Institute of Chemical Industry Testing Co., Ltd.



声明

Statement

1. 本报告无上海化工院检测有限公司检验检测专用章、二维码无效。

The report is invalid if it is not affixed the dedicated inspection and testing seal of Shanghai Research Institute of Chemical Industry Testing Co., Ltd. and QR Code on it.

2. 本报告复印件无效。

Copies of the report are invalid.

3. 本报告无编制、审核、批准人签字无效。

The report is invalid without the signatures of compiler, checker and approver.

4. 本报告涂改无效。

The report is invalid if it is forged or altered.

5. 本报告中的检验结论仅适用于收到的样品。

The inspection conclusion of this report only applies to the sample as received.

6. 除另有说明, 检测检验类别都是指委托分析。

Unless noted otherwise, the test type is consignation test.

7. 本报告的真伪性可登入本公司网站 http://www.ghs.cn 查询

The authenticity of the report can be checked via our website: http://www.ghs.cn.

地址: 上海市光复西路 2779 号接待大厅

Address: Reception Hall, Shanghai Research Institute of Chemical Industry Co., Ltd, No.2779 West Guangfu Road, Shanghai, China

邮政编码(Post Code): 200062

电话(Tel): (021) 31015134

网址 (web site): www.ghs.cn

电子信箱(E-mail): sds@ghs.cn

SI HUI PAK KO BATTERIES CO., LTD.

SAFETY DATA SHEET

Lithium Manganese Button Cell CR2025 PK 3V 150mAh

SECTION1 PRODUCT AND COMPANY IDENTIFICATION

Product name:

Lithium Manganese Button Cell CR2025 PK 3V 150mAh

Company:

SI HUI PAK KO BATTERIES CO., LTD.

Address:

No. 88 Cangfeng Avenue, Chengzhong District, Sihui City, Zhaoqing City,

Guangdong Province, 526200, P.R.China

Email:

Sd02@pakko.cn

Fax:

86-758-3325259

Emergency Phone:

86-758-3396189

Recommend use of the chemical and restrictions on use: /

SDS Number:

2621070158

Effective Date:

2021-08-18

SECTION2 HAZARDS IDENTIFICATION

The product is outside of the scope of GHS system.

Main Hazards:

Fire or Explosion Hazards:

Lithium metal emits spontaneously flammable gas in contact with water, and the electrolyte may contain flammable liquid.

Health Hazards:

Lithium metal is corrosive to eyes and skin, and may cause burns or corrosion in contact. The electrolyte in the battery causes skin irritation and eye irritation.

SECTION3 INFORMATION ON INGREDIENTS

Product name:

Lithium Manganese Button Cell CR2025 PK 3V 150mAh

| Ingredient | Concentration | CAS No. | EC No. |
|-------------------|---------------|-----------|-----------|
| Iron | 58. 62% | 7439-89-6 | 231-096-4 |
| Manganese dioxide | 31% | 1313-13-9 | 215-202-6 |
| Graphite | 3% | 7782-42-5 | 231-955-3 |

| Propylene carbonate | 2.5% | 108-32-7 | 203-572-1 |
|---------------------|--------|-----------|-----------|
| Lithium | 2.2% | 7439-93-2 | 231-102-5 |
| 1,2-Dimethoxyethane | 2. 18% | 110-71-4 | 203-794-9 |
| Lithium perchlorate | 0.5% | 7791-03-9 | 232-237-2 |

SECTION4 FIRST-AID MEASURES

Skin Exposure:

If in contact with the internal materials of battery, remove the contaminated clothing and footwear, immediately flush with plenty of water for at least 20 minutes. Call a physician.

Eye Exposure:

If in contact with the internal materials of battery, lift your eyelids immediately and rinse them with running water for more than 20 minutes. Call a physician.

Inhalation Exposure:

If the internal materials of battery are inhaled, immediately remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician.

Oral Exposure:

Do not induce vomiting if the internal materials of battery are swallowed. Call a physician immediately.

Most Important Symptoms/Effects, Acute and Delayed:

No data available.

Indication of Immediate Medical Attention and Special Treatment Needed, if Necessary:

No data available.

SECTION5 FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Suitable: Dry graphite powder, dry sand.

Specific Hazards Arising from the Chemical:

Lithium metal can ignite spontaneously in the air when heated to a molten state. It can release hydrogen and energy when reacting with water or acids, which causes fire or even explosion. A molten stream is generated immediately after burning and will disperse and emit thick white smoke, which will shade the fire scene.

Special Protective Action for Fire-fighters:

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Fire-extinguishing work is done from the windward. Uninvolved persons should evacuate to a safe place.

SECTION6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Use personal protective equipment. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Entry to noninvolved personnel should be controlled around the leakage area by roping off. Remove all sources of ignition. Water treatment is strictly prohibited. Cut off the source of leakage as much as possible.

Environmental Precautions:

Avoid leakage getting into the earth, ditches or waters.

Methods and Materials for Containment and Cleaning up:

In case of small leakage, use dry sand or other non-combustible materials to cover the leakage, and then cover with plastic cloth to reduce scattering and avoid raining. In case of powder leakage, cover the leakage with plastic cloth or canvas to reduce scattering. Keep it dry, and remove it under the guidance of an expert.

SECTION7 HANDLING AND STORAGE

Precautions for Safe Handling:

Operators should be trained and strictly abide by operating procedures. Wear appropriate protective clothing and safety gloves. Keep away from ignition sources, heat and flame. No smoking at working site. Handling is performed in an explosion-proof ventilation system and equipment. Do not let the lithium metal contact with water. Avoid disassembling the battery at will and reversing battery polarity within the battery assembly. The battery must be firmly packed in inner packaging so as to effectively prevent short circuits and short circuits caused by movement. In case of leakage of the materials in the battery, avoid directly contacting with eyes and skin. Avoid inhalation. Incompatibilities: Acids. Halogens, Combustible materials and Corrosive substances.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in a cool, dry, and well-ventilated area. Keep away from ignition sources, heat and flame. Avoid exposure to moisture. Incompatibilities: Acids. Halogens, Combustible materials and Corrosive substances. The battery must be firmly packed in inner packaging so as to effectively prevent short circuits and short circuits caused by movement. Storage place should be equipped with appropriate varieties and quantities of fire fighting equipment and leakage emergency treatment equipment.

SECTION8 EXPOSURE CONTROL/PPE

Control Parameters:

GBZ 2.1-2019 Occupational Exposure Limits for Hazardous Agents in the Workplace - Part 1: Chemical Hazardous Agents:

Manganese and its inorganic compounds (calculated as MnO_2): PC-TWA 0.15 mg/m² Graphite dust: PC-TWA 4 mg/m² (Total dust); PC-TWA 2 mg/m² (Inhalable dust)

Manganese dioxide: TLV-TWA 0.2 mg (Mn)/nu

Graphite: TLV-TWA 2 mg/m

Appropriate Engineering Controls:

Mechanical exhaust required. Safety shower and eye bath.

Individual Protection Measures:

Eye/Face Protection:

Wear chemical safety glasses.

Skin Protection:

Hand Protection: Wear safety gloves.

Body Protection: Wear appropriate protective clothing.

Respiratory Protection:

Wear government approved respirator if needed.

Thermal Hazards:

No data available.

Other Protect:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION9 PHYSICAL/CHEMICAL PROPERTIES

Appearance:

Silvery button metal shell

Odor:

Odorless

pH Value:

8-9

Solubility:

Partial soluble in water

Boiling Point,

No data available

Initial Boiling

Point and Boiling

Range: Melting

>300℃

Point/Freezing

Point:

Flash Point

No data available

(Closed Cup):

Density/Relative

No data available

Density:

Kinematic

No data available

Viscosity:

Lower/Upper

No data available

Explosion

Limit/Flammabili

tv Limit:

Vapour Pressure:

No data available

Relative Vapor

No data available

Density:

Partition

No data available

Coefficient

N-Octanol/Water(

Log Value):

Autoingnition

No data available

Temperature:

Decomposition

No data available

Temperature:

Particle

No data available

characteristics:

Flammability

No data available

(Solid, Gas):

SECTION10 STABILITY AND REACTIVITY

Reactivity:

No data available.

Chemical Stability:

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions:

No data available.

Conditions to Avoid:

Avoid misoperation, exposure to heat and open flame. Avoid mechanical or electrical abuse and overcharge. Prevent short circuits. Prevent movement which could lead to short circuits. Avoid exposure to moisture.

Incompatible Materials:

Acids, Halogens, Combustible materials and Corrosive substances.

Hazardous Decomposition Products:

Carbon oxides, metal oxides, etc.

SECTION11 TOXICOLOGICAL INFORMATION

Acute Toxicity:

No data available.

Skin Corrosion/Irritation:

Lithium metal is corrosive to skin, and may cause burns or corrosion in contact. The electrolyte in the battery causes skin irritation.

Serious Eye Damage/Irritation:

Lithium metal is corrosive to eyes, and may cause burns or corrosion in contact. The electrolyte in the battery causes eye irritation.

Respiratory Sensitization:

No data available.

Skin Sensitization:

No data available.

Carcinogenicity:

No data available.

Germ Cell Mutagenicity:

No data available.

Reproductive Toxicity:

No data available.

Specific Target Organ Toxicity -Single Exposure:

No data available.

Specific Target Organ Toxicity -Repeated Exposure:

No data available.

Aspiration Hazard:

No data available.

SECTION12 ECOLOGICAL INFORMATION

Toxicity:

No data available.

Persistence and Degradability:

No data available.

Bioaccumulative Potential:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects:

No data available.

SECTION13 DISPOSAL CONSIDERATION

Disposal Methods:

The disposal of discarded battery shall comply with the requirements of relevant laws, regulations, policies and standards such as the "Law of the People's Republic of China on the Prevention and Control of Environmental Pollution by Solid Waste" and "Technical Policy for the Prevention and Control of Waste Battery Pollution". Contact a licensed professional waste disposal service to dispose of wastes. Used battery being transported for disposal or reclamation should be carefully checked prior to shipment to ensure the integrity of each battery and its suitability for transport.

SECTION14 TRANSPORT INFORMATION

Only Lithium Metal Battery during Transport:

> The product has passed the test items of UN Model Regulations, Manual of Test and Criteria Section 38.3 and UN Model Regulations, SP188, 1.2m drop test. The net weight of the lithium batteries in the package is less than 2.5 kg. The content of Lithium is less than 1 g.

RTD/ADR (2019)

The product is not subject to RID/ADF according to special provision 188.

Edition):

According to 2.2.9.1.7 (g) of RID/ADk (2019 Edition), Manufacturers and subsequent distributors of cells or batteries manufactured shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph

IATA DGR (62nd Edition):

The product shall meet the General Requirements and section II of Packaging Instruction

968.

According to 3.9.2.6.1(g) of IATA DGR (62nd Edition), Manufacturers and subsequent distributors of cells or batteries manufactured after 30 June 2003 shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

IMO IMDG Code

The product is not subject to IMO IMDG Code according to special provision 188.

(2018 Edition): According to 2.9.4.7 of IMO IMDG Code (2018 Edition), Manufacturers and subsequent distributors of cells or batteries manufactured shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38. 3. 5.

SECTION15 REGULATORY INFORMATION

Domestic Regulations:

Only Lithium Metal Battery during Transport:

Regulations Concerning Road Transportation of Dangerous Goods (JT/T 617-2018) :

UN Number: 3090 Name and Description: Lithium metal batteries

The product has passed the test items of UN Model Regulations, Manual of Test and Criteria Section 38.3. The product is not subject to JT/T 617-2018 according to special provision 188.

List of Dangerous Goods (GB 12268-2012):

UN Number: 3090 Proper Shipping Name: Lithium metal batteries

The product has passed the test items of UN Model Regulations, Manual of Test and Criteria Section 38.3, The product is not subject to GB 12268-2012 according to special provision 188.

List of Dangerous Goods by Rail (2009 Edition):

Number: 91013 Name of Product: Lithium batteries

International Regulations:

Directive 2006/66/EC and 2013/56/EU:

The label, disposal and recycling of the battery shall meet the requirements of EU Directive 2006/66/EC and 2013/56/EU.

ICAO TI:

- 1. Unless be exempted according to ICAO TI, the lithium ion cell/batteries (UN 3480, PI 965) and lithium metal cell/batteries (UN 3090, PI 968) are forbidden for carriage on passenger aircraft.
- 2. Unless be approved according to ICAO TI, Lithium ion cells/batteries (UN 3480, PI 965) must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated design capacity.
- 3. A shipper is not permitted to offer for transport more than one (1) package prepared according to Section II of PI 965 and PI 968 in any single consignment. Not more than one (1) package prepared in accordance with Section II of PI 965 and PI 968 may be placed into an overpack.
- 4. Packages prepared according to Section II of PI 965 and PI 968 must be offered to the operator separately from other cargo and must not be loaded into a unit load device (ULD) before being offered to the operator.

SECTION16 OTHER INFORMATION

Preparation Date:

2021-08-18

Preparation Department:

Shanghai Research Institute of Chemical Industry Testing Co., Ltd. Tel(Fax):+86-21-52815377/31765555

Revision:

0

Abbreviations and Acronyms:

CAS: Chemical Abstracts Service EC: European Commission ACGIH: American Conference of Governmental Industrial Hygienists PC-TWA: Permissible concentration—time weighted average TLV-TWA: Time weighted average threshold limit RID: Regulations concerning the International Carriage of Dangerous Goods by Rail ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IATA DGR: International Air Transport Association Dangerous Goods Regulations IMO IMDG CODE: International Maritime Organization International Maritime Code for Dangerous Goods EU: European Union ICAO T1: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air PI: Packaging Instruction

Other Information:

This SDS is compiled based on the information such as ingredients provided by the applicant and our current knowledge. This SDS shall be used only as a guide. The users of this SDS must make independent judgments on the correctness and completeness and then decide its suitability according to the actual situation. The users should take the relevant legal responsibilities for the consequences of use.





X