

Installed in a few minutes

Step 1 - Apply the self-adhesive Velcro tape to the inside of your door frame.

Step 2 - Attach the door seal to the Velcro strip.

Step 3 - Open the zipper and attach your air conditioning hose to the door seal.

Step 4 - Close the zipper firmly around the hose. Use cable ties for better fixation.



The energy-saving mounting solution for air conditioners.
The door seal is fixed with the supplied Velcro tape.
The door seal can be removed without leaving any residue at any time.



Application

The Hot Air Stop is suitable for all doors up to a size of 87x200 cm.

Scope of delivery


1x Hot Air Stop
1x Velcro strap

Guarantee

2 years



Dimensions



**8m White Velcro Tape
Good Sealing**



Technical data

- Suitable for doors with a maximum size of 87x200 cm.
- The door seal for air conditioners is a practical helper and can be attached to the balcony door in a few easy steps. Simply stick the supplied adhesive tape into the door frame, attach the door seal to the door frame and you are done.
- Sealing the door increases the cooling capacity of the local air conditioning system. This reduces the general energy consumption as the room can be cooled faster.
- The zipper system allows you to continue to use the door comfortably even when the air conditioning is on. At the same time, however, it offers perfect protection against insects (like a fly screen) and also prevents moisture from penetrating.
- Due to the two zipper openings, the door seal is suitable for all portable air conditioners regardless of the manufacturer.
- Easy installation without drilling without additional tools.
- The material is durable, UV resistant, water repellent and washable at 40°C.
- EAN: 9005151000924

Subject to technical changes, errors and colour variations



Scheringgasse 3
1140 Vienna, Austria
Phone +43 1 970 21-0
www.she.at