



## Highlights

- **50 kW heat output** for rapid heating of large rooms up to 500 m<sup>2</sup>
- **High air flow rate of 1,500 m<sup>3</sup>/h** Distributes the warm air evenly
- **safety** with overheating protection, flame monitoring
- **Large 38 litre tank** for long running times with only 4.6 litres consumption per hour
- **Stainless steel combustion chamber** for reliable and long-lasting operation
- **IPX4 protection class** Splash-proof for everyday use on construction sites

## Lieferumfang

- Heating gun
- Operating instructions

### Mobile diesel I forced air heater with 50 kW - effective heat for large spaces

This powerful diesel I forced air heater is ideal for heating large areas quickly and reliably - for example in workshops, warehouses or on construction sites. With a heat output of 50 kW and an air flow rate of 1,500 m<sup>3</sup>/h, it ensures that pleasant temperatures are achieved even in cool environments.

The forced air heater can be operated with diesel or paraffin and is equipped with a durable stainless steel combustion chamber. An integrated fan supports heat distribution and keeps the device running reliably. Additional protection is provided by functions such as automatic switch-off in the event of overheating, flame monitoring with fuel stop and a thermocouple for temperature control.

The desired temperature can be conveniently set using the built-in control panel. A permanently installed oil level indicator provides an overview of the fill level of the 38 litre tank at all times. With a consumption of around 4.6 litres per hour, longer operation is also possible without any problems.

Thanks to the robust castors, the appliance is easy to transport and can be used flexibly. With protection class IPX4, it is also protected against splash water, making it ideal for demanding environments.

**Ideal for areas up to 500 m<sup>2</sup> - reliable, safe and mobile.**



Front view




Oblique view



Side view

### Specifications:

- 50KW heat output
- Operation with diesel or paraffin possible
- Stainless steel combustion chamber with fan-assisted cooling
- 38 litre tank capacity
- Fuel consumption: approx. 4.6 litres per hour





# Diesel forced air heater 50KW

SHXDO50KW

## Garantiezeit

- 2 years


- Air flow rate: 1,500 m<sup>3</sup>/h
- Suitable for areas up to 500 m<sup>2</sup>
- With overheating protection
- Flame monitoring (flame-out fuel cut)
- Thermocouple
- Integrated control panel for temperature setting
- Permanently installed oil level indicator for a quick overview
- Efficient motor: Motor output of 280 W
- IPX4 protection class
- With 2 wheels for easy transport

## Dimensions:

- Product (W×H×D): 900×600×530 mm
- Packaging (W×H×D): 917×480×403 mm
- Net/gross weight: 21,36 kg / 24,1 kg

Österreichische  
Marke

Technische Änderungen, Irrtümer und  
Farbschwankungen vorbehalten. Ursprungsland,  
wenn nicht anders angegeben: China



9005151008746

 **SCHUSS**  
HOME ELECTRONIC

Schuss Home Electronic GmbH,  
Scheringgasse 3, 1140 Wien,  
+43 (1) 970 21 - 0