



HOT AIR STOP - WINDOW

SHE01AIRSTPFE

Installed in a few minutes

Step 1 - Apply the self-adhesive Velcro tape to the inside of your window frame.

Step 2 - Attach the window seal to the Velcro tape.

Step 3 - Open the zipper and attach your air conditioning hose to the window seal.

Step 4 - Close the zipper firmly around the hose.



The energy-saving mounting solution for air conditioners.
The window seal is fixed with the supplied Velcro tape.
The window seal can be removed without residue at any time.

Scope of delivery

1x Hot Air Stop
1x Velcro Tape

Warranty period

2 years

Technical data

- Fits all standard window constructions, whose total circumferential dimension does not exceed 400 cm
- Easy and fast assembly
- The acquisition costs are reduced by the energy saving paid off by itself.
- Durable, water-repellent material
- Convenient opening or closing of the window without dismantling the Hot Air Stop is possible at any time.
- Hot Air Stop is washable at max. 40°C.
- Practical use of Hot Air Stop is also possible for exhaust air dryers, both in the warm and cold season.
- EAN: 9005665024348

Österreichische
Marke

Technische Änderungen, Fehler und Farbschwankungen vorbehalten



SCHUSS
HOME ELECTRONIC

Scheringgasse 3
1140 Wien
Telefon +43 1 970 21-0
www.she.at